

## HF05 Series

Trade Encapsulator  
Optional Stand



### DESCRIPTION

An exceptional quality, heavy duty range of machines for encapsulation of any small to large format posters, banners, signage, graphics etc. with the facility to mount on to board up to 5mm thick. The machines are suitable for use with a wide range of hot and cold films (an optional rewind device is required to run on cold film products) making them very versatile on a whole range of different printed stock. The range comprises of four models from 370mm (A3), through to the larger 1100mm (A0) catering for all common print formats. With simple to use controls and user friendly design the machines are delivered 'ready-to-go' and even the beginner can quickly achieve professional results with very little training. The highfield encapsulator range makes light work of any long or short run encapsulation jobs enhancing production in any modern print room and 'on-demand' production environment.

### FEATURES

- Rear safety cut off knife
- Emergency cut off switch
- Works film thickness 30-250 micron
- Optional stand on castors
- Suitable for use with hot and cold films
- Roller pressure adjustment
- Reverse function
- Optional Rewind unit
- Meets and exceeds CE safety standards
- Easy loading system incorporating drop down idler bars
- Mounts up to 5mm thick boards
- Variable speed up to 5 meters per minute
- Teflon coated heat shoes
- 3 year warranty on parts

### TECHNICAL SPECIFICATIONS

| Model                     | HF0537 - A3         | HF0554 - A2         | HF0581 - A1         | HF05110 - A0+       |
|---------------------------|---------------------|---------------------|---------------------|---------------------|
| <b>Weight</b>             | 30kg                | 40kg                | 60kg                | 85kg                |
| <b>Max Film Width</b>     | 360mm               | 530mm               | 800mm               | 1100mm              |
| <b>Max Film Thickness</b> | 250 micron          | 250 micron          | 250 micron          | 250 micron          |
| <b>Max Item Thickness</b> | 5mm                 | 5mm                 | 5mm                 | 5mm                 |
| <b>Dimensions Boxed</b>   | 740 x 640 x 570mm   | 960 x 640 x 570mm   | 1360 x 640 x 570mm  | 1460 x 640 x 570mm  |
| <b>Variable Speed</b>     | 0-5 meters per min. | 0-5 meters per min. | 0-5 meters per min. | 0-5 meters per min. |
| <b>Voltage</b>            | 220 VAC 10amp       | 220 VAC 10amp       | 220 VAC 10amp       | 220 VAC 10amp       |